
ACJT1235-8C 12A TRIAC

Rev.A.1.1

DESCRIPTION:

The ACJT1235-8C triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in applications such as heating regulation, induction motor starting circuits, for phase control operation in light dimmers, motor speed controllers. The ACJT1235-8C embeds a TVS structure to absorb the inductive turn-off energy such as those described in the IEC 61000-4-5 standards. Package TO-220C is RoHS compliant.



MAIN FEATURES

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Storage junction temperature range	T_{stg}	-40-150	
Operating junction temperature range	T_j	-40-125	
Repetitive peak off-state voltage (T_j=25)	V_{DRM}	=2j EMC /P <</MCID 26 >>stDoce re6.11T0056dTc(0)0	

Peak pulse voltage (T_j=25 ; non-repetitive,off-state;FIG.7)	V_{pp}	5	kV

ELECTRICAL CHARACTERISTICS (T_j=25 unless otherwise specified)

Symbol	Test Condition	Quadrant	Value		Unit
I_{GT}	V_D =12V R_L =33Ω	- -	MAX.	35	mA
V_{GT}		- -	MAX.	1	V
V_{GD}	D DRM L	- -	MIN.	0.2	V
I_L	I_G =1.2I_{GT}				
				70	
I_H	I_T =500mA		MAX.	45	mA
dV/dt	V_D=540V Gate Open T_j =125		MIN.	1000	V/μs
(dI/dt)c	(dV/dt)c=20V/μs, T_j=125		MIN.	15	A/ms
t_{on}	I_G=40mA I_A=200mA I_R=20mA T_j=25		TYP.	3	μs
t_{off}				30	
V_{CL}	I_{CL}=0.1mA t_p=1ms		MIN.	850	V

STATIC CHARACTERISTICS

Symbol	Parameter		Value(MAX.)	Unit
V_{TM}	I_{TM} =17A t_p=380μs	T_j=25	1.45	V
V_{TO}	Threshold voltage	T_j=125	0.8	V
R_D	Dynamic resistance	T_j=125	34	mΩ
I_{DRM}	V_D =V_{DRM} V_R =V_{RRM}	T_j=25	5	μA
I_{RRM}		T_j=125	0.5	mA

THERMAL RESISTANCES

Symbol	Parameter	Value	Unit
$R_{th(j-c)}$	junction to case (AC)	1.3	/W
$R_{th(j-a)}$	junction to ambient (AC)	60	/W

FIG.1: Maximum power dissipation versus RMS on-state current




FIG.2: RMS on-state current versus case temperature





FIG.3: Surge peak on

FIG.7 Test circuit for inductive and resistive loads to IEC-61000-4-5 standards



ORDERING INFORMATION

Order code	Voltage V_{DRM}/V_{RRM} (V)	IGT(mA)	Package	Base qty. (pcs)	Delivery mode
AA					