JX075K 12A Sensitive SCR

Rev.A.1.1

The JX075K SCR provides high dV/dt rate with strong resistance to electromagnetic interface. It is especially recommended for use on residual current circuit breaker, straight hair, igniter etc. Package TO-252 is RoHS compliant.

Symbol	Value	Unit
$I_{T(RMS)}$	12	A
V_{DRM} /V_{RRM}	800	V
I_{GT}	Ò200	εA

Parameter	Symbol	Value	Unit
Storage junction temperature range	T_{stg}	-40-150	
Operating junction temperature range	T_j	-40-110	
Repetitive peak off-state voltage (T_j=25)	V_{DRM}	800	V
Repetitive peak reverse voltage (T_j=25)	V_{RRM}	800	V
Average on-state current (T_C 37)	$I_{T(AV)}$	7.5	A
RMS on-state current (T_C 37)	$I_{T(RMS)}$		

Peak gate power	P_{GM}	10	W
Peak pulse voltage (T_j=25 ; non-repetitive,off-state;FIG.8)	V_{pp}	0.5	kV

(T_j=25 unless otherwise specified)

Symbol	Test Condition	Value			Unit
		MIN.	TYP.	MAX.	
I_{GT}	V_D=12V R_L=33q	-	60	200	εA
V_{GT}		-	-	0.8	V
V_{GD}	V_D=V_{DRM} T_j=110	0.2	-	-	V
I_L	I_G=1.2 I_{GT}	-	-	6	mA
I_H	I_T=0.05A	-	-	5	mA
dV/dt	V_D=540V T_j=25 R_{GK}=1kq	50	-	-	V/εs
	V_D=540V T_j=25 R_{GK}=220q	200	-	-	
t_{on}	I_G=10mA I_A=20mA I_R=2mA T_j=25	-	2	-	εs
t_{off}		-	70	-	εs

Symbol	Parameter		Value(MAX.)	Unit
V_{TM}	I_T=24A t_p=380εs	T_j=25	1.6	V
V_{TO}	Threshold voltage	T_j=110	0.9	V
R_D	Dynamic Resistance	T_j=110	0.02	q
I_{DRM}	V_D=V_{DRM} V_R=V_{RRM}	T_j=25	5	εA
I_{RRM}		T_j=110	0.5	mA

Symbol	Parameter	Value	Unit
$R_{th(j-c)}$	junction to case (DC)	4.5	/W
$R_{th(j-a)}$	junction to ambient (DC)	120	/W

J X 075 K -/

- J: JieJie Microelectronics Co., Ltd.
- X: Sensitive gate SCRs
- 075: $I_{T(AV)}$:7.5A
- K: K:TO-252
- -/: Blank: Tube; -TR: Tape & Reel




FIG.1: Maximum power dissipation versus RMS on-state current





FIG.2: RMS on-state current versus case temperature

FIG.8 Test circuit for inductive and resistive loads to IEC-61000-4-5 standards.



Ref.	Dimensions Millimeters	Inches



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement. Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.