T0835H-8E 8A TRIAC

Rev.A.1.1

DESCRIPTION:

[illegible]

MAIN FEATURES

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
[illegible]	T_{stg}	[illegible]	
[illegible]	T_j	[illegible]	[illegible]

[illegible] (T$_j$ [illegible] ; [illegible] - [illegible] - [illegible] 8)	V_p	3	kV

ELECTRICAL CHARACTERISTICS (T$_j$ [illegible]

Symbol

ORDERING INFORMATION



MARKING





FIG.1:



FIG.2: (RMS)

FIG.7: [illegible]



[illegible]


1.2/50μS voltage surge
8/20μS current surge
R_S
2Ω
R
6Ω
L
13μH
R_G
300Ω

ORDERING INFORMATION

Order code	Voltage V_{DRM}/V_{RRM} (V)	IGT(mA)	Package	Base qty. (pcs)	Delivery mode
		- -			
T0835H-8E	800	35	TO- - 35H-		

PACKAGE MECHANICAL DATA

[illegible]	[illegible]					
	[illegible]			[illegible]		
	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
A	[illegible]		[illegible]	[illegible]		[illegible]
B	[illegible]		[illegible]	[illegible]		[illegible]
C	[illegible]		[illegible]	[illegible]		[illegible]
D	[illegible]			[illegible]		
E	[illegible]		[illegible]	[illegible]		[illegible]
F	[illegible]		[illegible]	[illegible]		[illegible]