T1650H-6A 16A TRIAC

Rev.A.1.1

DESCRIPTION:

The T1650H-6A triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in applications such as heating regulation, induction motor starting circuits, for phase control operation in light dimmers, motor speed controllers. Compared to traditional triacs, T1650H-6A provides a very high switching capability up to junction temperatures of 150°C. By using an internal ceramic pad, T1650H-6A provides a rated insulation voltage of 2500 VRMS, complying with UL staAVR7.18FL.at:pE2 5Tw 906).w 27.18 0 Td ( )Tj54(T)1 (1)]T-21 0 T

FIG.1: Maximum power dissipation versus RMS on-state current




FIG.2: RMS on-state current versus case temperature




FIG.3: Surge peak on-state current versus number of cycles

FIG.4: On-state characteristics

T1650H-6A

ORDERING INFORMATION

Order code	Voltage V_{DRM}/V_{RRM} (V)	IGT(mA)	Package	Base qty. (pcs)	Delivery mode
		- -			
T1650H-6A	600	50	TO-220A(Ins)	50	Tube

Document Revision History

Date	Revision	Changes
Apr.10, 2023	A.1.0	Last updated
Oct.11, 2025	A.1.1	Revise PACKAGE MECHANICAL DATA