

J
ST
04
A
-800
CW
JieJie Microelectronics Co., Ltd.
Triacs
IT(RMS):4A
A:TO-220A(Ins)
800:VDRM /VRRM ≥ 800V
CW:IGT1-3 ≤ 35mA



JST04A
800CW
XXX XXX
XXX XXX
Year
Month
Production
Code

FIG.1: Maximum power dissipation versus RMS on-state current




FIG.2: RMS on-state current versus case temperature

Order code	Voltage V_{DRM}/V_{RRM} (V)	IGT(mA)	Package	Base qty. (pcs)	Delivery mode
		- -			
JST04A-800CW	800	35	TO-220A(Ins)	50	Tube

Document Revision History

Date	Revision	9 Cha /TT3 1 Tf 0.001474.6e87.4 rw 1(356 0 0 Tm [(D)

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.