## JST08A-600B 8A TRIAC

Rev.A.1.1

## DESCRIPTION:

The JST08A-600B triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in applications such as heating regulation, induction motor starting circuits, for phase control operation in light dimmers, motor speed controllers. By using an internal ceramic pad, JST08A-600B provides a rated insulation voltage of 2500 VRMS, complying with UL standards (File ref: E252906). Package TO-220A is RoHS compliant.

## MAIN FEATURES

| Symbol | Value | Unit |
|---|---|---|
| $I_{T(RMS)}$ | 8 | A |
| $V_{DRM}$ /$V_{RRM}$ | 600 | V |
| $I_{GT}$ / / / | 50/50/50/70 | mA |

## ABSOLUTE MAXIMUM RATINGS

| Parameter | | Symbol | Value | Unit |
|---|---|---|---|---|
| Storage junction temperature range | | $T_{stg}$ | -40-150 | |
| Operating junction temperature range | | $T_j$ | -40-125 | |
| Repetitive peak off-state voltage ($T_j$=25 ) | | $V_{DRM}$ | 600 | V |
| Repetitive peak reverse voltage ($T_j$=25 ) | | $V_{RRM}$ | 600 | V |
| RMS on-state current ($T_C$ 97 ) | | $I_{T(RMS)}$ | 8 | A |
| Non repetitive surge peak on-state current (full cycle , $t_p$=20ms , $T_j$=25 ) | | $I_{TSM}$ | 80 | A |
| Non repetitive surge peak on-state current (full cycle , $t_p$=16.6ms , $T_j$=25 ) | | | 88 | |
| $I^2t$ value for fusing ($t_p$=10ms , $T_j$=25 ) | | $I^2t$ | 32 | $A^2s$ |
| Critical rate of rise of on-state current ($I_G$=2 $I_{GT}$ , f=100Hz , $T_j$=125 ) | - | dI/dt | 100 | A/μs |
| | - | | 50 | |
| Peak gate current ($t_p$=20μs , $T_j$=125 ) | | $I_{GM}$ | 4 | A |
| Average gate power dissipation ($T_j$=125 ) | | $P_{G(AV)}$ | 0.5 | W |
| Peak gate power | | $P_{GM}$ | 10 | W |

| | | | |
|---|---|---|---|
| Peak pulse voltage ($T_j$=25 ; non-repetitive,off-state;FIG.7) | $V_{pp}$ | 1 | kV |

## ELECTRICAL CHARACTERISTICS ($T_j$=25 unless otherwise specified)

| Symbol | Test Condition | Quadrant | Value | | Unit |
|---|---|---|---|---|---|
| $I_{GT}$ | $V_D$=12V $R_L$=33Ω | - - | MAX. | 50 | mA |
| | | | | 70 | |
| $V_{GT}$ | | ALL | MAX. | 1 | V |
| $V_{GD}$ | $V_D$=$V_{DRM}$ $T_j$=125 $R_L$=3.3kΩ | ALL | MIN. | 0.2 | V |
| $I_L$ | $I_G$=1.2$I_{GT}$ | - - | MAX. | 50 | mA |
| | | | | 100 | |
| $I_H$ | $I_T$=200mA | | MAX. | 60 | mA |
| dV/dt | $V_D$=400V Gate Open $T_j$=125 | | MIN. | 1200 | V/μs |
| (dV/dt)c | (dI/dt)c=3.5A/ms, $T_j$=125 | | MIN. | 12 | V/μs |
| $t_{on}$ | $I_G$=80mA $I_A$=400mA $I_R$=40mA $T_j$=25 | | TYP. | 5 | μs |
| $t_{off}$ | | | | 30 | |

## STATIC CHARACTERISTICS

| Symbol | Parameter | | Value(MAX.) | Unit |
|---|---|---|---|---|
| $V_{TM}$ | $I_{TM}$=11A $t_p$=380μs | $T_j$=25 | 1.5 | V |
| $V_{TO}$ | Threshold voltage | $T_j$=125 | 0.81 | V |
| $R_D$ | Dynamic resistance | $T_j$=125 | 44 | mΩ |
| $I_{DRM}$ | $V_D$=$V_{DRM}$ $V_R$=$V_{RRM}$ | $T_j$=25 | 5 | μA |
| $I_{RRM}$ | | $T_j$=125 | 0.25 | mA |

## THERMAL RESISTANCES

| Symbol | Parameter | Value | Unit |
|---|---|---|---|
| $R_{th(j-c)}$ | junction to case (AC) | 2.5 | /W |
| $R_{th(j-a)}$ | junction to ambient (AC) | 60 | /W |

## ORDERING INFORMATION




**FIG.1:** Maximum power dissipation versus RMS on-state current



**FIG.2:** RMS on-state current versus case temperature

**JST08A-600B** **JieJie M**


## ORDERING INFORMATION

| Order code | Voltage $V_{DRM}/V_{RRM}$ (V) | IGT(mA) | | Package | Base qty. (pcs) | Delivery mode |
|---|---|---|---|---|---|---|
| | | - - | | | | |
| JST08A-600B | 600 | 50 | 70 | TO-220A(Ins) | 50 | Tube |

### Document Revision History

| Date | Revision | Changes |
|---|---|---|
| Apr.14, 2023 | A.1.0 | Last updated |
| Oct.13, 2025 | A.1.1 | Revise PACKAGE MECHANICAL DATA |

## PACKAGE MECHANICAL DATA



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.
Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.