JST12F-1000CW 12A TRIAC

Rev.A.1.1

DESCRIPTION:

The JST12F-1000CW triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in applications such as heating regulation, induction motor starting circuits, for phase control operation in light dimmers, motor speed controllers. JST12F-1000CW snubberless triac is especially recommended for use on inductive loads. By using an external plastic package,

Peak gate power	P_{GM}	10	W
Peak pulse voltage (T_j=25 ; non-repetitive,off-state;FIG.7)	V_{pp}	4.5	kV

ELECTRICAL CHARACTERISTICS (T_j=25 unless otherwise specified)

Symbol	Test Condition	Quadrant	Value		Unit
I_{GT}	V_D =12V R_L =33Ω	- -	MAX.	35	mA
V_{GT}		- -	MAX.	1	V
V_{GD}	V_D =V_{DRM} T_j =125 R_L =3.3kΩ	- -	MIN.	0.2	V
I_L	I_G =1.2I_{GT}	-	MAX.	50	mA
				60	
I_H	I_T =500mA		MAX.	35	mA
dV/dt	V_D=670V Gate Open T_j =125		MIN.	500	V/μs
(dI/dt)c	(dV/dt)c=20V/μs T_j=125		MIN.	10	A/ms
t_{on}	I_G=40mA I_A=200mA I_R=20mA T_j=25		TYP.	3	μs
t_{off}				30	


STATIC CHARACTERISTICS

Symbol	Parameter		Value(MAX.)	Unit
V_{TM}	I_{TM} =17A t_p=380μs	T_j=25	1 .5	V
V_{TO}	Threshold voltage	T_j=125	0 .77	V
R_D	Dynamic resistance	T_j=125	35	mΩ
I_{DRM}	V_D =V_{DRM} V_R =V_{RRM}	T_j=25	8	μA
I_{RRM}		T_j=125	1	mA

THERMAL RESISTANCES

Symbol	Parameter	Value	Unit
$R_{th(j-c)}$	junction to case (AC)	2.4	/W
$R_{th(j-a)}$	junction to ambient (AC)	60	/W

ORDERING INFORMATION



MARKING




FIG.1: Maximum power dissipation versus RMS on-state current




FIG.2: RMS on-state current versus case temperature



FIG.7 ÖTest circuit for inductive and resistive loads to IEC-61000-4-5 standards




	Package	Base qty. (pcs)	Delivery mode
	TO-220F(Ins)	50	Tube

vision History

nges			
10	0	N	µ ,

PACKAGE MECHANICAL DATA



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document