JST136W-800T 1A TRIAC

Rev.A.1.1

DESCRIPTION:

The JST136W-800T triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in applications such as heating regulation, induction motor starting circuits, for phase control operation in

ELECTRICAL CHARACTERISTICS (T_j=25 unless otherwise specified)

Symbol	Test Condition	Quadrant	Value		Unit
I_{GT}	V_D=12V R_L=33Ω	ALL	MAX.	5	mA
V_{GT}		ALL	MAX.	1.3	V
V_{GD}	V_D=V_{DRM} T_j=125 R_L=3.3kΩ	ALL	MIN.	0.2	V
I_L	I_G=1.2I_{GT}	-	MAX.	10	mA
		-		15	
I_H	I_T=100mA		MAX.	5	mA
dV/dt	V_D=540V Gate Open T_j=110		MIN.	20	V/μs
(dV/dt)c	(dI/dt)c=1.8A/ms, T_j=110		MIN.	1	V/μs
t_{on}	I_G=10mA y3Tc -0.00404 224.52 535917.92 553.32 105.84 0.004 Tw 1.14 0 Td [(0m)-Td				

ORDERING INFORMATION





FIG.7: Relative variations of gate trigger current, holding current and latching current versus junction temperature



JST136W-800T

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.
Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.
is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.
Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.